



Networking & Telecommunications End-to End Solutions

Copper Structured Cabling Category 6 UTP IDC Patch Panels 1U 48 Ports



Linxcom UTP CAT6 patch panels are 19 inch rack mountable IDC/PCB moulded jack patch panels.

All panels comply with the EIA/TIA standard for Category 6 and are available in a choice of port density. Every patch panel is made with high quality materials, tested and certified by UL and 3P.



Features & Benefits

- ETL & 3P Certified
- 48 port Cat6 patch panel
- Space-saving high density 1U
- Meets or exceeds the requirement proposed by TIA /EIA 568 B .2 ,ISO/IEC 11801 Category 6
- Sturdy aluminium plate around jacks
- Phosphor bronze with 6-50 micro inches gold plated
- Available with colour-coded T568A and T658B wiring patterns
- Easy wiring installation, fit for 110 punch-down tools
- Termination accepts 22, 23, 24 and 26 AWG (0.64-0.4) solid wires
- Black electrostatic powder-coated corrosion-resistant steel

52/155 Mbps ATM (ATM Forum)

100 BASE-T4 (Fast Ethernet)

100 VG-Any LAN (IEEE802.12)

100 BASE-T (Fast Ethernet)

1 Gbps Ethernet (IEEE802.3)

Applications

- POTS, T1&Tq fractional
- ASDN basic & primary rate
- 4/16 Mbps Token Ring (IEEE802.5)
- 10 BASE-T (IEEE802.3)
- 100 Mbps TP-PMD

Colouring

Pair 1	Pair 2	Pair 3	Pair 4		
Blue, Blue/White	Orange, Orange/White	Green, Green/White	Brown, Brown/White		
Performance					
Insertion I	ife 750 cycles minimum				
IDC I	200 times (22-26 AWG solid wire) minimum				
Plug/Jack Contact Fo	ce 100g minimum using FCC-ap	100g minimum using FCC-approved plug			
Insulation Resistar	ce 100Mohms minimum	100Mohms minimum			
Contact Resistar	ce 7Mohms maximum	7Mohms maximum			
Dielectric Intens	ity AC 1000Vrms, 50Hz or 60Hz	AC 1000Vrms, 50Hz or 60Hz in 60s			
Plat	ng Gold (3u", 6u", 15u", 30u", 50	Gold (3u", 6u", 15u", 30u", 50u"), Silver (1.25um, 5um)			
Modula	rity 8-pin, 4-pair	8-pin, 4-pair			





Networking & Telecommunications End-to End Solutions

Copper Structured Cabling Category 6 UTP IDC Patch Panels 1U 48 Ports

Ordering Information

Using the available configurations amend/create a part number using the formula below.

0 0	1 5		
Construction		Panel Style	
UTP (Unshielded Twisted Pair) UTP		IDC/PCB IDCPP	
UTP	6	IDCPP	481U
Category		Port Density	
Category 6 (CAT6) 6		1U 48 Ports 481U	

Example: UTP6IDCPP481U - Category 6 Unshielded Twisted Pair 48 1U Port IDC Patch Panel

For any queries, please contact the Linxcom team using the details below.