



## Fibre Management

# Outdoor Splitter/Terminal Box – Model 3



Lincom Fibre Optic Terminal Boxes are light and compact whilst maintaining adequate fibre storage needs and minimum bend radii. Terminal Boxes can be wall, pole or rack-mounted and have a variety of core capacities and adapter types available. IP65 Rated, to withstand harsh conditions, UV and rainfall resistant.



Up to 24  
Fibres



IP65  
Rated





Wall  
Mountable

## Technical Specifications

Material	Cold-rolled steel
Ports (SC or FC/ST Simplex)	12 (or 6x SC Duplex)
Cable Entries	3 (1x PG21 – 13-18mm Ø, 2x PG9 – 4-8mm Ø)
Dimensions (mm)	250 * 230 * 70
Weight (kg)	2.0
Accessories	Cable Glands & Seals, Cable Ties, Splice Cassette, Splice Protection Sleeves, Wall Fixings, Cable Grips, FM Blocks ( <i>More Accessories Available</i> )
IP Rating	65

## Adapter Plates

Adapter Plate FC/ST Simplex	Adapter Plate SC Simplex
	

## Ordering Information

Using the available configurations amend/create product codes using the formula below.

Box Type		Fibre Type		Simplex / Duplex / Quad	
Outdoor Terminal Box	OTB	Unloaded	EM	Simplex	S
		Singlemode Loaded	SM	Duplex	D
		Multimode Loaded	MM	Quad (LC Only)	Q
		Singlemode APC Loaded	SMA		
OTB	3	EM	SC	S	12
Model		Adapter Type		Port Density	
Model 3	3	ST	ST	12 Ports	12
		SC	SC		
		FC	FC		
		LC	LC		

Example: **OTB3EMSCS12** - Unloaded SC Simplex 12 Port Outdoor Terminal Box Model 3